

●製品の仕様、付属品およびデザインは予告なく変更する場合があります。記載内容は 2021 年 1 月現在のものです。

顔認証端末 IRC-F1T331



- 3.97-inch touch screen, 2 Mega pixel wide-angle lens
- 2 MP 広角デュアルレンズ
- Face anti-spoofing
- 顔認証距離: 0.3m to 1.5m
- 深層学習アルゴリズム
- 300 face capacity, 1,500 card capacity (when connecting external card reader); 150,000 event capacity, and up to 20,000
- 顔認識期間<0.2秒/ユーザー;顔認識精度率≥99%
- Capture linkage and captured pictures storage
- スタンドアロンオペレーション
- Connects to one external card reader via RS-485 protocol
- Supports 6 attendance status, including check in, check out, break in, break out, overtime in, overtime out
- Supports multiple languages: English, Spanish, Arabic, Thai, Indonesian, Russian, and Vietnamese
- Supports EHome 5.0 (ISUP 5.0), and ISAPI protocol
- Configuration via web browser

■ 仕様

システムパラメーター

オペレーションシステム	Linux
カメラ	2 MP dual-lens camera with wide dynamic range
Capacity	Card: 1500 (When connecting external card reader) Face: 300 Event: 150,000
1:N face recognition duration	<0.2 s

液晶画面

液晶画面	3.97-inch touch screen
------	------------------------

一般

Face Recognition Distance	0.3m to 1.5m
インターフェース	USB×1, electric lock×1, door contact×1, tamper×1, exit button×1, RS-485×1
Communication Mode	TCP/IP (10/100 Mbps, self-adaptive)
Power supply	12V, 1.5A, 18W
Working temperature	-10°C to 50°C
Working humidity	10 to 90% (no condensing)
外形寸法	120mm×110mm×23mm
Application situation	Indoor use

■ 外観図

