


ECOHiLUX照明器具 配光データシート


器具品名	SB形人感センサ付き ダウンライト	保守率	
器具品番	LSB100-0635MSCAB-V5	良	0.69
部品品名	-	中	0.67
部品品番	-	否	0.63
器具光束	350lm	器具効率	
光源	-	上方向	0%
光源光束	一体型器具のため、器具光束表示	下方向	100%
		全方向	100%



照明率表

		作業面照明率(×0.01)																																
反射率(%)	天井	80								70								50								30				0				
	壁	70				50				30				10				70				50				30				10				0
	床	30	10	30	10	30	10	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0						
室 指 数	0.4	47	44	33	32	26	25	21	45	43	33	32	25	25	21	32	31	25	25	21	25	24	21	19										
	0.6	64	59	50	48	42	40	35	63	58	49	47	41	40	35	48	46	41	40	35	40	39	35	33										
	0.8	75	68	61	57	51	49	44	73	67	59	56	51	49	43	57	55	50	48	43	49	47	43	41										
	1	84	75	70	65	61	58	52	81	74	69	64	60	57	52	66	63	58	56	51	57	56	51	49										
	1.3	92	82	80	73	71	66	61	90	81	78	72	70	66	61	75	70	68	65	60	66	64	60	58										
	1.5	98	86	86	78	77	71	66	94	84	84	77	75	71	66	80	75	73	70	65	71	69	65	62										
	2	105	92	95	85	87	79	75	102	90	92	84	85	79	74	88	82	82	77	73	79	76	73	70										
	2.5	111	95	102	90	94	85	81	107	94	99	89	92	84	80	94	87	88	83	79	85	81	78	76										
	3	114	98	106	93	99	89	85	110	96	103	92	97	88	84	97	90	92	86	83	89	85	82	80										
	4	118	100	112	97	106	93	90	114	99	108	96	103	92	90	102	93	98	91	88	93	89	87	84										
5	121	102	115	99	111	96	94	117	101	112	98	108	95	93	105	96	102	94	92	97	92	90	88											
7	124	104	120	102	116	100	98	119	103	116	101	113	99	97	109	99	106	97	95	100	95	94	91											
10	126	106	123	104	121	103	101	122	104	119	103	117	102	100	111	101	110	100	98	103	98	97	94											

配光曲線



直射水平面照度

