


ECOHiLUX照明器具 配光データシート


器具品名	LEDスポットライト MiOL FOODEE	保守率	
器具品番	SPC23FI-EMW	良	0.69
部品品名	-	中	0.67
部品品番	-	否	0.63
器具光束	2300 lm	器具効率	
光源	-	上方向	0%
光源光束	一体型器具のため、器具光束表示	下方向	100%
		全方向	100%



照明率表

作業面照明率(×0.01)																											
反射率(%)	天井	80								70								50						30			0
	壁	70		50		30		10	70		50		30		10	50		30		10	30		10	0			
	床	30	10	30	10	30	10	10	30	10	30	10	30	10	10	30	10	30	10	10	30	10	10	0			
室指数	0.4	66	62	55	53	49	48	44	65	61	54	53	48	48	44	54	52	48	47	44	48	47	44	43			
	0.6	85	79	74	71	68	66	62	84	78	74	70	67	65	62	72	69	67	65	62	66	65	62	60			
	0.8	96	87	85	80	78	75	72	94	86	84	80	78	75	72	82	79	77	74	71	76	74	71	70			
	1	103	92	93	86	86	81	78	100	91	91	85	85	81	78	89	84	83	80	77	82	80	77	75			
	1.3	109	97	99	91	93	87	84	106	96	98	91	92	87	84	95	89	90	86	83	88	85	83	81			
	1.5	113	99	104	94	97	91	87	110	98	102	94	96	90	87	98	92	94	89	87	91	88	86	84			
	2	118	103	110	99	104	95	93	115	101	108	98	103	95	92	103	96	99	94	91	96	92	90	89			
	2.5	121	105	115	101	109	99	96	118	104	112	101	107	98	96	107	99	103	97	95	99	95	94	92			
	3	124	106	118	103	113	101	99	120	105	115	102	111	100	98	109	101	106	99	97	102	97	96	94			
	4	127	108	122	106	118	104	102	123	107	119	105	115	103	102	113	103	110	102	100	105	100	99	97			
	5	129	109	125	108	122	106	105	125	108	121	107	119	105	104	115	105	113	103	102	107	102	101	99			
7	131	110	129	109	126	109	108	127	109	125	108	123	108	107	117	106	116	106	105	110	104	103	101				
10	133	111	131	111	130	110	110	128	110	127	110	126	109	109	119	108	118	107	107	112	105	105	102				

配光曲線



直射水平面照度

