


# ECOHiLUX照明器具 配光データシート

## 意匠図


器具品名	LEDダウンライト LAシリーズ	保守率	
器具品番	DL75L308-15A6W-D DL75L308-15A6W-DLS	良	0.67
部品品名	-	中	0.63
部品品番	-	否	0.56
器具光束	5880lm	器具効率	
光源	-	上方向	0%
光源光束	一体型器具のため、器具光束表示	下方向	100%
		全方向	100%



## 照明率表

		作業面照明率(×0.01)																											
反射率	天井	80								70				50				30				0							
	壁	70		50		30		10		70		50		30		10		50		30		10		30		10		0	
床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0
室 指 数	0.4	58	54	46	44	39	39	35	57	54	46	44	39	39	35	45	43	39	38	35	39	38	35	33					
	0.6	77	71	65	61	57	56	52	75	70	64	61	57	55	51	62	60	56	55	51	56	55	51	50					
	0.8	88	80	76	72	69	66	62	86	79	75	71	68	66	62	73	70	67	65	62	66	65	61	60					
	1	96	86	85	79	77	73	69	93	85	83	78	77	73	69	81	77	75	72	69	74	72	69	67					
	1.25	103	91	93	85	85	80	76	100	90	91	84	84	80	76	88	83	82	79	76	80	78	75	73					
	1.5	107	94	98	89	91	84	81	104	93	96	88	90	84	81	92	87	87	83	80	85	82	79	78					
	2	113	98	105	94	99	90	87	110	97	103	93	97	90	87	98	91	94	88	86	91	87	85	83					
	2.5	117	101	110	97	104	94	91	113	99	107	96	102	93	91	102	94	98	92	90	94	90	89	87					
	3	119	102	113	99	108	96	94	115	101	110	98	105	95	93	104	96	101	94	92	97	93	91	89					
	4	122	104	117	102	113	99	97	118	103	114	101	110	98	97	108	99	105	97	95	100	95	94	92					
5	124	105	120	103	116	101	100	120	104	116	102	113	100	99	110	100	107	99	97	102	97	96	93						
7	126	106	123	105	120	103	102	122	105	119	104	117	103	101	112	102	110	101	100	104	99	98	95						
10	128	107	126	106	124	105	104	124	106	122	105	120	104	103	114	103	113	102	101	106	100	100	97						

## 配光曲線



## 直射水平面照度

