


ECOHiLUX照明器具 配光データシート

意匠図


| | | | |
|------|-----------------|------|------|
| 器具品名 | ベースダウンライト | 保守率 | |
| 器具品番 | DL4WW8-7A7BW-DA | 良 | 0.69 |
| 部品品名 | - | 中 | 0.67 |
| 部品品番 | - | 否 | 0.63 |
| | | 器具効率 | |
| 器具光束 | 357lm | 上方向 | 0% |
| 光源 | - | 下方向 | 100% |
| 光源光束 | 一体型器具のため、器具光束表示 | 全方向 | 100% |



照明率表

| | | 作業面照明率(×0.01) | | | | | | | | | | | | | | | | | | | | | | |
|-------------|------|---------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|
| 反射率 | 天井 | 80 | | | | | | | | 70 | | | | 50 | | | | 30 | | 0 | | | | |
| | 壁 | 70 | | 50 | | 30 | | 10 | | 70 | | 50 | | 30 | | 10 | | 30 | | 10 | 0 | | | |
| | 床 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 0 | | |
| 室 指 数 | 0.4 | 59 | 55 | 47 | 45 | 40 | 39 | 36 | 57 | 54 | 46 | 45 | 40 | 39 | 36 | 45 | 44 | 40 | 39 | 36 | 39 | 39 | 35 | 34 |
| | 0.6 | 77 | 71 | 65 | 62 | 58 | 56 | 52 | 76 | 70 | 65 | 62 | 58 | 56 | 52 | 63 | 61 | 57 | 56 | 52 | 56 | 55 | 52 | 50 |
| | 0.8 | 89 | 81 | 77 | 72 | 70 | 67 | 63 | 87 | 79 | 76 | 72 | 69 | 67 | 63 | 74 | 71 | 68 | 66 | 63 | 67 | 65 | 62 | 61 |
| | 1 | 96 | 86 | 85 | 79 | 78 | 74 | 70 | 94 | 85 | 84 | 79 | 77 | 74 | 70 | 82 | 77 | 76 | 73 | 70 | 74 | 72 | 69 | 68 |
| | 1.25 | 103 | 92 | 93 | 85 | 86 | 81 | 77 | 100 | 90 | 91 | 85 | 85 | 80 | 77 | 88 | 83 | 83 | 79 | 76 | 81 | 79 | 76 | 74 |
| | 1.5 | 107 | 95 | 98 | 89 | 91 | 85 | 81 | 105 | 94 | 96 | 88 | 90 | 84 | 81 | 93 | 87 | 88 | 83 | 81 | 85 | 83 | 80 | 78 |
| | 2 | 113 | 99 | 105 | 94 | 99 | 91 | 87 | 110 | 97 | 103 | 93 | 97 | 90 | 87 | 99 | 92 | 94 | 89 | 86 | 91 | 88 | 85 | 84 |
| | 2.5 | 117 | 101 | 110 | 97 | 104 | 94 | 91 | 113 | 100 | 107 | 96 | 102 | 93 | 91 | 102 | 95 | 98 | 92 | 90 | 95 | 91 | 89 | 87 |
| | 3 | 119 | 102 | 113 | 99 | 108 | 97 | 94 | 116 | 101 | 110 | 98 | 106 | 96 | 94 | 105 | 96 | 101 | 94 | 92 | 97 | 93 | 91 | 89 |
| | 4 | 123 | 104 | 118 | 102 | 113 | 100 | 98 | 119 | 103 | 114 | 101 | 110 | 99 | 97 | 108 | 99 | 105 | 97 | 96 | 100 | 96 | 94 | 92 |
| 5 | 124 | 105 | 120 | 103 | 117 | 102 | 100 | 120 | 104 | 117 | 102 | 113 | 101 | 99 | 110 | 100 | 108 | 99 | 98 | 102 | 97 | 96 | 94 | |
| 7 | 127 | 107 | 124 | 105 | 121 | 104 | 103 | 122 | 105 | 120 | 104 | 117 | 103 | 102 | 112 | 102 | 111 | 101 | 100 | 105 | 99 | 98 | 96 | |
| 10 | 128 | 107 | 126 | 106 | 124 | 106 | 105 | 124 | 106 | 122 | 105 | 120 | 104 | 104 | 114 | 103 | 113 | 103 | 102 | 106 | 101 | 100 | 97 | |

配光曲線



直射水平面照度

