


ECOHiLUX照明器具 配光データシート

意匠図


器具品名	ダウンライト	保守率	
器具品番	IRLDDL15L30-60D1W	良	-
部品品名	-	中	-
部品品番	-	否	-
		器具効率	
器具光束	1320lm	上方向	0%
光源	-	下方向	100%
光源光束	一体型器具のため、器具光束表示	全方向	100%



照明率表

反射率	天井	80								70				50			30			0					
		壁	70		50		30		10		70	50	30	10	50	30	10	30	10	10	30	10	10	0	
	床	30	10	30	10	30	10	10	30	10	30	10	30	10	10	30	10	10	30	10	10	30	10	10	0
室 指 数	0.4	59	55	48	47	43	42	38	58	55	48	46	42	38	47	46	42	41	38	42	41	38	37		
	0.6	80	73	70	66	64	62	59	78	72	69	66	63	61	58	68	65	63	61	58	62	61	58	57	
	0.8	86	78	75	71	69	66	63	84	77	75	70	68	66	62	73	69	67	65	62	66	65	62	60	
	1	93	83	83	77	77	73	69	91	82	82	77	76	72	69	80	75	74	72	69	73	71	69	67	
	1.25	100	89	91	83	85	80	77	97	87	90	83	84	79	77	87	82	82	79	76	80	78	76	74	
	1.5	102	90	94	85	88	81	78	100	89	92	85	87	81	78	89	83	84	80	78	82	79	77	75	
	2	107	93	100	89	94	86	83	104	92	98	88	92	85	83	93	87	89	84	82	86	83	81	79	
	2.5	111	96	105	92	100	90	88	108	94	102	92	98	89	87	97	90	94	88	86	90	87	85	83	
	3	113	97	107	94	103	92	90	109	96	105	93	100	91	89	99	91	96	90	88	92	88	87	85	
	4	116	98	111	96	107	94	93	112	97	108	95	105	94	92	102	93	100	92	91	95	91	89	87	
5	118	99	114	98	111	96	95	114	98	110	97	108	95	94	104	95	102	94	93	97	92	91	89		
7	120	101	117	99	115	98	97	116	99	113	98	111	98	97	106	97	105	96	95	99	94	93	91		
10	121	101	119	101	118	100	99	117	100	115	100	114	99	98	108	98	107	97	97	101	95	95	92		

配光曲線



直射水平面照度

