


ECOHiLUX照明器具 配光データシート

意匠図


器具品名	ダウンライト	保守率	
器具品番	DL50WW-50MUW-D	良	0.78
部品品名	-	中	0.74
部品品番	-	否	0.70
器具光束	5950lm	器具効率	
光源	-	上方向	0%
光源光束	一体型器具のため、器具光束表示	下方向	100%
		全方向	100%



照明率表

反射率	天井	80								70				50				30				0							
	壁	70		50		30		10		70		50		30		10		50		30		10		30		10		0	
	床	30	10	30	10	30	10	10	30	10	30	10	30	10	10	30	10	30	10	10	30	10	10	30	10	10	0	0	
室指数	0.4	59	55	47	46	41	40	36	58	55	47	45	40	40	36	46	45	40	39	36	40	39	36	34					
	0.6	78	71	65	62	58	56	52	76	70	65	62	58	56	52	63	61	57	56	52	56	55	52	50					
	0.8	88	80	77	72	69	66	62	86	79	75	71	68	66	62	73	70	67	65	61	66	65	61	60					
	1	96	86	84	78	77	73	69	93	85	83	78	76	72	68	80	76	74	72	68	73	71	68	66					
	1.25	102	91	92	84	84	79	75	100	90	90	83	83	79	75	87	82	81	78	74	79	77	74	72					
	1.5	107	94	97	88	90	83	79	104	93	95	87	88	83	79	91	86	86	82	78	83	81	78	76					
	2	113	98	104	93	97	89	85	109	97	102	92	96	88	85	97	90	92	87	84	89	86	83	81					
	2.5	117	101	109	96	103	93	90	113	99	106	95	101	92	89	101	94	97	91	88	93	89	87	85					
	3	119	102	113	99	107	96	93	115	101	110	98	105	95	92	104	96	100	93	91	96	92	90	88					
	4	123	104	118	102	113	99	97	119	103	114	101	110	98	96	108	99	105	97	95	100	95	94	91					
5	125	106	121	104	117	102	100	121	105	117	103	114	101	99	110	100	108	99	97	102	97	96	93						
7	128	107	125	106	122	104	103	123	106	120	105	118	103	102	113	103	111	101	100	105	100	99	96						
10	130	108	127	107	125	107	106	125	107	123	106	121	105	105	115	104	114	103	103	107	102	101	98						

配光曲線



直射水平面照度

