


ECOHiLUX照明器具 配光データシート

器具品名	直管型LEDランプ 専用器具 直付下面開放型.	保守率	
器具品番	IRLDLFL41CL-K	良	0.81
部品品名	-	中	0.77
部品品番	-	否	0.67
器具効率			
器具光束	2240lm	上方向	0%
光源	LDG32T-N/16/25/16S	下方向	90%
光源光束	2500lm	全方向	90%


意匠図




照明率表

作業面照明率(×0.01)																0								
反射率	天井	80				70				50				30										
	壁	70	50	30	10	70	50	30	10	50	30	10	30	10	30	10	0							
	床	30	10	30	10	30	10	30	10	30	10	10	30	10	30	10	0							
室 指 数	0.4	41	39	28	27	21	21	16	40	38	28	27	21	20	16	20	20	16	15					
	0.6	57	52	43	40	34	33	28	55	51	42	40	34	33	28	40	39	33	32	27	26			
	0.8	66	60	52	48	42	41	35	64	59	51	48	42	40	35	49	46	41	40	34	32	32		
	1	74	67	60	56	50	48	42	72	65	59	55	50	47	42	56	53	48	47	42	46	41	39	
	1.25	82	73	69	63	59	56	50	79	71	67	62	58	55	50	64	60	56	54	49	55	53	49	46
	1.5	87	77	74	68	65	60	55	84	75	72	67	64	60	54	69	65	62	59	54	60	58	53	51
	2	95	82	83	74	75	68	63	91	81	81	73	73	67	62	77	71	70	66	62	67	65	61	58
	2.5	100	86	90	79	82	74	69	96	84	87	78	80	73	68	82	76	76	72	68	73	70	67	64
	3	103	88	94	83	87	78	73	99	87	91	81	85	77	73	86	79	81	75	71	77	74	70	68
	4	108	92	100	87	94	83	79	104	90	97	86	91	82	78	91	83	87	80	77	82	79	76	73
	5	111	94	105	90	99	86	83	106	92	101	89	96	85	82	95	86	91	83	81	86	82	79	77
	7	114	96	109	93	105	90	88	110	94	106	92	102	89	87	99	90	96	87	85	90	86	84	81
	10	117	98	113	96	110	93	92	112	96	109	94	106	92	91	102	92	100	90	89	94	89	87	84

配光曲線




直射水平面照度



ECOHiLUX照明器具 配光データシート

意匠図

器具品名	直管型LEDランプ 専用器具 逆富士型	保守率	
		良	0.81
器具品番	IRLDLFL41FJ-K	中	
		否	0.77
部品品名	-	否	
		器具効率	
器具光束	2300lm	上方向	8%
		下方向	84%
光源	LDG32T-N/16/25/16S	全方向	92%
光源光束	2500lm		




照明率表


作業面照明率(×0.01)

反 射 率	天井	80				70				50				30				0						
		壁		70	50	30	10	70		50	30	10	50		30	10	30		10	0				
		床		30	10	30	10	30	10	30	10	10	30	10	30	10	30	10	10	0				
室 指 数	0.4	43	41	29	28	22	21	17	42	39	29	28	21	21	17	27	26	21	20	16	14			
	0.6	59	55	44	42	35	34	29	57	53	43	41	35	34	28	41	39	33	32	28	32	31	27	24
	0.8	69	63	54	50	44	42	36	66	61	52	49	43	41	35	49	47	41	40	35	39	38	34	31
	1	78	70	62	58	52	50	43	74	67	61	57	51	49	43	57	54	49	47	42	46	45	40	37
	1.25	86	76	71	65	61	57	51	82	74	69	64	60	56	50	65	61	57	54	49	54	52	48	
	1.5	91	80	77	70	67	62	56	87	78	75	68	65	61	55	70	65	62	59	54	59	57	52	48
	2	99	86	87	77	77	70	64	94	83	83	76	75	69	64	77	72	70	66	62	66	64	60	56
	2.5	104	90	93	83	85	76	71	99	87	90	81	82	75	70	83	77	77	72	68	72	69	65	61
	3	108	92	98	86	90	80	75	103	90	94	84	87	79	74	87	80	81	76	72	76	73	69	65
	4	113	96	105	90	97	86	81	107	93	100	88	94	84	80	92	84	87	81	77	81	78	75	70
	5	116	98	109	93	103	89	85	110	95	104	91	99	88	84	96	87	91	84	81	85	81	78	73
	7	120	100	114	97	109	94	91	114	98	109	95	105	92	89	100	91	97	88	86	89	85	83	78
	10	122	102	118	100	115	97	95	117	100	113	98	110	95	93	104	94	101	92	90	93	88	86	81

配光曲線




直射水平面照度



ECOHiLUX照明器具 配光データシート

意匠図

器具品名	直管型LEDランプ 専用器具 トラフ型	保守率	
器具品番	IRLDLFL41TR-K	良	0.81
部品品名	-		0.77
部品品番	-		0.67
器具効率			
器具光束	2300lm	上方向	8%
光源	LDG32T-N/16/25/16S	下方向	84%
光源光束	2500lm	全方向	92%




照明率表


作業面照明率(×0.01)

反 射 率	天井	80				70				50				30				0						
		壁		70	50	30	10	70		50	30	10	50		30	10	30		10	0				
	床	30	10	30	10	30	10	30	10	30	10	10	30	10	30	10	30	10	0					
室 指 数	0.4	43	41	29	28	22	21	17	42	39	29	28	21	21	17	27	26	21	20	16	14			
	0.6	59	55	44	42	35	34	29	57	53	43	41	35	34	28	41	39	33	32	28	32	31	27	24
	0.8	69	63	54	50	44	42	36	66	61	52	49	43	41	35	49	47	41	40	35	39	38	34	31
	1	78	70	62	58	52	50	43	74	67	61	57	51	49	43	57	54	49	47	42	46	45	40	37
	1.25	86	76	71	65	61	57	51	82	74	69	64	60	56	50	65	61	57	54	49	54	52	48	44
	1.5	91	80	77	70	67	62	56	87	78	75	68	65	61	55	70	65	62	59	54	59	57	52	48
	2	99	86	87	77	77	70	64	94	83	83	76	75	69	64	77	72	70	66	62	66	64	60	56
	2.5	104	90	93	83	85	76	71	99	87	90	81	82	75	70	83	77	77	72	68	72	69	65	61
	3	108	92	98	86	90	80	75	103	90	94	84	87	79	74	87	80	81	76	72	76	73	69	65
	4	113	96	105	90	97	86	81	107	93	100	88	94	84	80	92	84	87	81	77	81	78	75	70
	5	116	98	109	93	103	89	85	110	95	104	91	99	88	84	96	87	91	84	81	85	81	78	73
	7	120	100	114	97	109	94	91	114	98	109	95	105	92	89	100	91	97	88	86	89	85	83	78
	10	122	102	118	100	115	97	95	117	100	113	98	110	95	93	104	94	101	92	90	93	88	86	81

配光曲線




直射水平面照度



ECOHiLUX照明器具 配光データシート

意匠図


器具品名	直管型LEDランプ 専用器具 埋込下面開放型	保守率	
器具品番	IRLDLFL41UK-K	良	0.81
部品品名	-		0.77
部品品番	-		0.67
器具効率			
器具光束	2300lm	上方向	0%
光源	LDG32T-N/16/25/16S	下方向	93%
光源光束	2500lm	全方向	93%




照明率表

作業面照明率(×0.01)																		
反射率	天井	80				70				50				30				
	壁	70	50	30	10	70	50	30	10	50	30	10	30	10	30	10	0	
	床	30	10	30	10	30	10	30	10	30	10	10	30	10	30	10	0	
室 指 数	0.4	39	37	27	26	20	19	15	38	36	26	25	20	19	15	19	15	14
	0.6	54	50	40	38	32	31	26	52	48	40	38	32	31	26	38	37	24
	0.8	63	57	49	46	40	39	33	61	56	48	45	40	38	33	46	44	30
	1	71	64	57	53	48	46	40	68	62	56	52	47	45	40	53	51	37
	1.25	78	69	66	60	56	53	47	75	68	64	59	55	52	47	61	57	44
	1.5	83	73	71	64	62	57	52	80	72	69	63	61	57	52	66	62	48
	2	90	78	80	71	71	65	60	87	77	70	70	64	59	73	68	67	56
	2.5	95	82	86	76	78	70	66	92	81	83	75	76	70	65	79	73	61
	3	98	84	90	79	83	74	70	95	83	87	78	81	73	69	82	76	65
	4	103	87	96	83	90	79	75	99	86	93	82	87	78	75	87	80	70
5	106	89	100	86	95	82	79	102	88	96	85	92	81	78	90	82	87	73
	7	109	92	104	89	100	86	84	105	90	101	88	97	85	83	94	86	82
	10	112	93	108	91	105	89	87	107	92	104	90	102	88	87	97	88	77

配光曲線




直射水平面照度



ECOHiLUX照明器具 配光データシート

意匠図


器具品名	直管型LEDランプ 専用器具 直付下面開放型	保守率	
		良	0.81
器具品番	IRLDLFL42CL-K	中	
		否	0.77
部品品名	-	否	
		器具効率	
器具光束	4650lm	上方向	0%
		下方向	93%
光源	LDG32T-N/16/25/16S	全方向	93%
光源光束	2500lm × 2	上方向	0%
		下方向	93%




照明率表

反射率	天井	作業面照明率(×0.01)												0	
		80			70			50			30				
		壁	70	50	30	10	70	50	30	10	50	30	10		
室 指 数	床	30	10	30	10	30	10	30	10	30	10	30	10	0	
	0.4	44	41	30	29	22	22	17	42	40	30	29	22	17	
	0.6	60	55	45	43	36	35	30	58	54	45	42	36	35	
	0.8	70	64	55	52	45	43	37	68	62	54	51	45	43	
	1	79	71	64	59	54	51	45	76	69	63	58	53	51	
	1.25	87	78	73	67	63	59	53	84	76	71	66	62	59	
	1.5	93	82	79	72	69	64	58	89	80	77	71	68	64	
	2	101	87	89	79	79	73	67	97	86	86	78	78	72	
	2.5	106	91	96	85	87	79	73	102	90	93	83	85	78	
	3	110	94	100	88	93	83	78	106	92	97	87	90	82	
4	114	97	107	92	100	88	84	110	96	103	91	97	87	83	
5	118	99	111	95	105	92	88	113	98	107	94	102	91	87	
7	121	102	116	99	112	96	93	117	100	112	98	108	95	92	
10	124	104	120	101	117	99	97	119	102	116	100	113	98	95	

配光曲線




直射水平面照度



ECOHiLUX照明器具 配光データシート

意匠図


器具品名	直管型LEDランプ 専用器具 逆富士型	保守率	
器具品番	IRLDLFL42FJ-K	良	0.81
部品品名	-	中	
部品品番	-	否	0.67
器具効率		器具効率	
器具光束	4650lm	上方向	4%
光源	LDG32T-N/16/25/16S	下方向	90%
光源光束	2500lm × 2	全方向	94%




照明率表

作業面照明率(×0.01)																	
反射率	天井	80				70				50				30			
	壁	70	50	30	10	70	50	30	10	50	30	10	30	10	10	0	
	床	30	10	30	10	30	10	30	10	30	10	10	30	10	10	0	
室 指 数	0.4	42	39	29	28	21	21	17	40	38	28	27	21	17	27	26	
	0.6	57	53	43	41	35	34	28	55	51	42	40	34	33	28	32	
	0.8	67	61	52	49	43	41	36	65	59	51	48	42	41	35	40	
	1	75	67	61	57	51	49	43	72	66	59	55	50	48	42	47	
	1.25	83	74	70	64	60	56	51	80	72	68	63	59	56	50	57	
	1.5	88	77	75	68	66	61	55	85	76	73	67	64	60	55	53	
	2	95	83	84	75	75	69	63	92	81	82	74	74	68	63	67	
	2.5	101	87	91	80	83	74	70	97	85	88	79	80	73	69	76	
	3	104	89	95	83	88	78	74	100	87	92	82	85	77	73	86	
	4	108	92	101	88	95	83	79	104	90	98	86	92	82	79	86	
5	111	94	105	90	100	87	83	107	92	101	89	96	85	82	94	86	
	7	115	96	110	94	106	91	88	110	95	106	92	102	89	87	98	89
	10	117	98	114	96	111	94	92	113	97	109	95	107	93	91	101	90

配光曲線




直射水平面照度



ECOHiLUX照明器具 配光データシート

意匠図


器具品名	直管型LEDランプ 専用器具 トラフ型	保守率	
		良	0.81
器具品番	IRLDLFL42TR-K	中	
		否	0.67
部品品名	-	器具効率	
器具光束	4600lm	上方向	0%
光源	LDG32T-N/16/25/16S	下方向	92%
光源光束	2500lm × 2	全方向	92%




照明率表

作業面照明率(×0.01)																0		
反射率	天井	80				70				50				30				
	壁	70	50	30	10	70	50	30	10	50	30	10	30	10	10	30		
室 指 数	床	30	10	30	10	30	10	30	10	30	10	10	30	10	10	30	10	0
	0.4	40	38	27	27	20	20	16	39	37	27	26	20	20	16	26	25	14
	0.6	56	51	42	39	33	32	27	54	50	41	39	33	32	27	39	38	25
	0.8	65	59	51	47	41	39	34	63	57	49	47	41	39	34	47	45	31
	1	73	65	59	54	49	47	41	70	64	57	54	48	46	41	55	52	38
	1.25	81	72	67	62	58	54	48	78	70	66	61	57	54	48	62	59	45
	1.5	86	75	73	66	63	59	53	82	74	71	65	62	58	53	67	63	49
	2	93	81	82	73	73	66	61	89	79	79	72	71	66	60	75	70	56
	2.5	98	84	88	78	80	72	67	94	83	85	77	78	71	66	80	74	62
	3	101	87	92	81	85	76	71	97	85	89	80	83	75	70	84	77	66
指 数	4	106	90	98	85	92	81	77	102	88	95	84	89	80	76	89	82	71
	5	109	92	102	88	97	84	81	105	90	99	87	94	83	80	92	84	74
	7	112	94	107	91	103	88	85	108	93	103	90	99	87	85	93	85	78
	10	115	96	111	94	108	92	89	110	95	107	93	104	90	89	100	90	82

配光曲線




直射水平面照度



ECOHiLUX照明器具 配光データシート

意匠図


器具品名	直管型LEDランプ 専用器具 埋込下面開放型	保守率	
器具品番	IRLDLFL42UK-K	良	0.81
部品品名	-	中	
部品品番	-	否	0.67
器具効率		器具効率	
器具光束	4800lm	上方向	0%
光源	LDG32T-N/16/25/16S	下方向	95%
光源光束	2500lm × 2	全方向	95%




照明率表

作業面照明率(×0.01)																	30			0					
反射率	天井	80						70						50						30			0		
	壁	70		50		30		10		70		50		30		10		50		30		10		0	
	床	30	10	30	10	30	10	10	30	10	30	10	30	10	10	10	30	10	30	10	10	30	10	10	0
室 指 数	0.4	42	40	29	28	21	21	16	41	39	28	27	21	21	16	27	27	21	20	16	20	20	16	15	
	0.6	58	53	43	41	35	34	28	56	52	43	41	34	33	28	41	40	34	33	28	33	32	28	26	
	0.8	68	62	53	50	43	41	35	66	60	52	49	43	41	35	50	47	42	40	35	41	40	35	33	
	1	76	68	62	57	52	49	43	74	67	60	56	51	48	43	57	54	49	48	42	48	47	42	40	
	1.25	84	75	70	65	61	57	51	81	73	69	64	60	56	50	66	62	58	55	50	56	54	50	47	
	1.5	89	79	76	69	66	62	56	86	77	74	68	65	61	55	71	66	63	60	55	61	59	54	52	
	2	97	85	86	76	76	70	64	94	83	83	75	75	69	64	79	73	72	68	63	69	66	62	60	
	2.5	103	88	92	82	84	76	70	99	87	90	80	82	75	70	85	78	78	73	69	75	72	68	65	
	3	106	91	97	85	89	79	75	102	89	94	84	87	79	74	88	81	83	77	73	79	75	72	69	
	4	111	94	103	89	97	85	81	107	93	100	88	94	84	80	94	86	89	82	79	84	80	78	75	
	5	114	96	107	92	102	88	85	110	95	104	91	99	87	84	97	89	93	86	83	88	84	81	79	
	7	118	99	113	96	108	93	90	113	97	109	94	105	92	89	102	92	98	90	88	93	88	86	83	
	10	120	101	117	98	113	96	94	116	99	112	97	109	95	93	105	95	102	93	91	96	91	90	87	

配光曲線




直射水平面照度



ECOHiLUX照明器具 配光データシート

意匠図

器具品名	直管型LEDランプ 専用器具 埋込下面開放型	保守率	
器具品番	IRLDLFL44UK-K	良	0.81
部品品名	-	中	0.77
部品品番	-	否	0.67
器具効率			
器具光束	8560lm	上方向	0%
光源	LDG32T-N/16/25/16S	下方向	86%
光源光束	2500lm × 4	全方向	86%




照明率表


作業面照明率(×0.01)

反射率	天井	80						70						50						30						0	
		壁		70		50		30		10		70		50		30		10		50		30		10		0	
	床	30	10	30	10	30	10	10	30	10	30	10	30	10	10	30	10	30	10	30	10	10	30	10	10	30	10
室 指 数	0.4	46	43	32	31	25	24	20	45	42	32	31	25	24	20	31	30	24	24	20	24	24	20	18			
	0.6	64	59	50	47	41	40	35	62	58	49	47	41	39	34	47	45	40	39	34	39	38	34	32			
	0.8	75	68	60	57	51	49	43	72	66	59	56	50	49	43	57	54	49	48	43	48	47	43	41			
	1	84	75	70	65	61	58	52	81	74	69	64	60	57	52	66	63	58	56	52	57	56	51	49			
	1.25	92	82	80	73	71	66	61	89	80	78	72	70	66	61	75	70	68	65	60	66	64	60	58			
	1.5	98	86	86	78	77	71	66	94	84	84	77	76	71	66	80	75	73	70	65	71	69	65	62			
	2	105	91	95	85	87	79	74	102	90	92	84	85	78	74	88	82	82	77	73	79	76	72	70			
	2.5	110	95	101	89	94	85	80	106	93	98	88	92	84	80	93	86	88	82	79	84	81	78	76			
	3	113	97	105	92	99	88	84	109	96	102	91	96	87	84	97	89	92	86	83	88	84	81	79			
	4	117	100	111	96	105	92	89	113	98	107	95	102	92	89	101	93	97	90	87	93	88	86	83			
	5	120	101	114	98	110	95	93	116	100	111	97	106	94	92	104	95	101	93	90	96	91	89	86			
	7	123	103	119	101	115	99	96	118	102	115	100	111	98	96	107	97	105	96	94	99	94	92	90			
	10	125	105	122	103	119	101	100	121	103	118	102	115	100	99	110	99	108	98	97	102	96	95	92			

配光曲線




直射水平面照度



ECOHiLUX照明器具 配光データシート

器具品名	直管型LEDランプ 専用器具 埋込下面開放型	保守率	
器具品番	IRLDLFL44UK-LVK	良	0.81
部品品名	-	中	0.77
部品品番	-	否	0.67
器具効率			
器具光束	8770lm	上方向	0%
光源	LDG32T-N/16/25/16S	下方向	88%
光源光束	2500lm × 4	全方向	88%

意匠図




照明率表

作業面照明率(×0.01)

反射率	天井	80						70						50						30						0		
		壁		70		50		30		10		70		50		30		10		50		30		10		0		
	床	30	10	30	10	30	10	10	30	10	30	10	30	10	10	30	10	30	10	30	10	10	30	10	10	30	10	0
室 指 数	0.4	46	44	33	32	26	25	21	45	43	33	32	26	25	21	32	31	25	25	21	25	24	21	19				
	0.6	65	60	51	48	42	41	36	63	58	50	48	42	41	36	48	46	41	40	35	40	40	35	33				
	0.8	75	68	61	57	52	50	44	73	67	60	57	51	49	44	58	55	50	49	44	49	48	44	42				
	1	84	76	71	65	61	58	53	82	74	69	65	61	58	53	67	63	59	57	52	58	56	52	50				
	1.25	93	82	80	73	71	67	62	90	81	78	73	70	66	61	75	71	68	65	61	66	64	60	58				
	1.5	98	86	86	78	77	72	67	95	84	84	77	76	71	66	80	75	73	70	66	71	69	65	63				
	2	105	91	95	85	87	79	75	102	90	92	84	85	79	74	88	82	82	77	73	79	76	73	70				
	2.5	110	95	101	89	94	85	81	106	93	98	88	92	84	80	93	86	88	82	79	84	81	78	76				
	3	113	97	105	92	99	88	84	109	96	102	91	96	87	84	97	89	92	86	82	88	84	81	79				
	4	117	100	111	96	105	92	89	113	98	107	95	102	91	88	101	92	97	90	87	92	88	86	83				
5	120	101	114	98	109	95	92	116	100	111	97	106	94	92	104	95	101	92	90	95	91	89	86					
	7	123	103	119	101	115	98	96	118	102	115	100	111	97	95	107	97	105	96	94	99	94	92	89				
	10	125	105	122	103	119	101	99	120	103	118	102	115	100	98	110	99	108	98	97	102	96	95	92				

配光曲線



直射水平面照度

