


ECOHiLUX照明器具 配光データシート

意匠図


| | | | |
|------|-------------------|------|------|
| 器具品名 | ベースダウンライト | 保守率 | |
| 器具品番 | DL24WW8-15A6BW-DA | 良 | 0.69 |
| 部品品名 | - | 中 | 0.67 |
| 部品品番 | - | 否 | 0.63 |
| 器具光束 | 2142lm | 器具効率 | |
| 光源 | - | 上方向 | 0% |
| 光源光束 | 一体型器具のため、器具光束表示 | 下方向 | 100% |
| | | 全方向 | 100% |



照明率表

| | | 作業面照明率(×0.01) | | | | | | | | | | | | | | | | | | | | | | |
|-------------|------|---------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|
| 反射率 | 天井 | 80 | | | | | | | | 70 | | | | 50 | | | | 30 | | 0 | | | | |
| | 壁 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 50 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 0 | | | | | |
| 床 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 0 | | | |
| 室 指 数 | 0.4 | 64 | 60 | 53 | 51 | 47 | 46 | 42 | 63 | 59 | 52 | 51 | 46 | 46 | 42 | 52 | 50 | 46 | 45 | 42 | 46 | 45 | 42 | 41 |
| | 0.6 | 83 | 76 | 72 | 68 | 65 | 63 | 60 | 81 | 75 | 71 | 68 | 65 | 63 | 60 | 70 | 67 | 64 | 63 | 60 | 63 | 62 | 59 | 58 |
| | 0.8 | 93 | 85 | 83 | 78 | 76 | 73 | 70 | 92 | 84 | 82 | 77 | 76 | 73 | 69 | 80 | 76 | 74 | 72 | 69 | 73 | 72 | 69 | 68 |
| | 1 | 100 | 90 | 90 | 84 | 83 | 79 | 76 | 98 | 89 | 89 | 83 | 83 | 79 | 76 | 86 | 82 | 81 | 78 | 75 | 80 | 78 | 75 | 73 |
| | 1.25 | 106 | 94 | 97 | 89 | 91 | 85 | 82 | 104 | 93 | 95 | 88 | 89 | 85 | 82 | 92 | 87 | 87 | 84 | 81 | 85 | 83 | 81 | 79 |
| | 1.5 | 110 | 97 | 102 | 92 | 95 | 88 | 85 | 107 | 96 | 100 | 91 | 94 | 88 | 85 | 96 | 90 | 91 | 87 | 85 | 89 | 86 | 84 | 82 |
| | 2 | 115 | 100 | 108 | 96 | 102 | 93 | 91 | 112 | 99 | 105 | 96 | 100 | 93 | 90 | 101 | 94 | 97 | 91 | 89 | 94 | 90 | 89 | 87 |
| | 2.5 | 119 | 102 | 112 | 99 | 107 | 96 | 94 | 115 | 101 | 109 | 98 | 105 | 96 | 94 | 104 | 97 | 101 | 94 | 93 | 97 | 93 | 92 | 90 |
| | 3 | 121 | 104 | 115 | 101 | 110 | 99 | 96 | 117 | 102 | 112 | 100 | 108 | 98 | 96 | 107 | 98 | 103 | 96 | 95 | 99 | 95 | 94 | 92 |
| | 4 | 124 | 105 | 119 | 103 | 115 | 102 | 100 | 120 | 104 | 116 | 102 | 113 | 101 | 99 | 110 | 101 | 107 | 99 | 98 | 102 | 98 | 97 | 94 |
| 5 | 126 | 106 | 122 | 105 | 119 | 103 | 102 | 122 | 105 | 118 | 104 | 116 | 103 | 101 | 112 | 102 | 110 | 101 | 100 | 104 | 99 | 98 | 96 | |
| 7 | 128 | 108 | 125 | 107 | 123 | 106 | 105 | 124 | 106 | 121 | 106 | 119 | 105 | 104 | 114 | 104 | 113 | 103 | 102 | 107 | 101 | 101 | 99 | |
| 10 | 130 | 108 | 128 | 108 | 126 | 107 | 107 | 125 | 107 | 124 | 107 | 122 | 106 | 106 | 116 | 105 | 115 | 104 | 104 | 108 | 102 | 102 | 99 | |

配光曲線



直射水平面照度

