


## ECOHiLUX照明器具 配光データシート

器具品名	ベースダウンライト	保守率		
		良	0.69	
器具品番	DL14L38-10W4BW-D	中	0.67	
	DL14L38-10W4BW-DLS			
部品品名	—	否	0.63	
	—			
部品品番	—	器具効率		
	—			
器具光束	1290lm	上方向	0%	
光源	—	下方向	100%	
光源光束	一体型器具のため、器具光束表示	全方向	100%	


意匠圖



## 照明率表

		作業面照明率(×0.01)																						
反射率	天井	80						70						50						30				
	壁	70		50		30		10	70		50		30		10	50		30		10	30		10	
	床	30	10	30	10	30	10	10	30	10	30	10	30	10	10	30	10	30	10	10	30	10	10	
室指 数	0.4	58	55	46	45	40	39	35	57	54	46	45	40	39	35	45	44	39	39	35	39	38	35	34
	0.6	77	70	64	61	57	55	51	75	69	64	61	57	55	51	62	60	56	55	51	55	54	51	49
	0.8	87	79	76	71	68	65	61	85	78	74	70	67	65	61	72	69	66	64	61	65	64	60	59
	1	95	85	83	77	76	72	68	92	84	82	77	75	71	67	80	75	73	71	67	72	70	67	65
	1.25	101	90	91	83	83	78	74	99	89	89	83	82	78	74	86	81	80	77	74	78	76	73	71
	1.5	106	93	96	87	89	83	79	103	92	94	86	88	82	78	91	85	85	81	78	83	80	77	75
	2	112	97	103	93	97	88	85	109	96	101	92	95	88	85	97	90	92	87	84	89	85	83	81
	2.5	116	100	109	96	102	92	89	112	99	106	95	100	92	89	101	93	96	90	88	93	89	87	85
	3	119	102	112	98	107	95	92	115	100	109	97	104	94	92	104	95	100	93	91	96	91	90	87
	4	122	104	117	101	112	99	97	118	103	114	100	110	98	96	107	98	104	96	95	99	95	93	91
	5	124	105	120	103	116	101	99	120	104	116	102	113	100	99	110	100	107	99	97	102	97	96	93
	7	127	107	124	105	121	104	103	123	106	120	104	117	103	102	113	102	111	101	100	105	99	98	96
	10	129	108	122	107	125	106	105	124	107	122	106	121	105	104	115	104	113	103	102	107	101	101	98

## 配光曲線



### 直射水平面照度

