


ECOHiLUX照明器具 配光データシート

意匠図


品名	ラインルクス	保守率	
セット品番	LX175F-40N-TR110T	良	0.83
		中	0.81
器具品名	トラフ型	否	0.77
器具品番	LXBF-TR110T	器具効率	
器具光束	4000lm	上方向	4%
光源	LXU175F-40N-110T	下方向	96%
光源光束	4000lm	全方向	100%



照明率表

		作業面照明率(×0.01)															
反射率	天井	80								70							
	壁	70				50				30				10			
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10
室 指 数	0.4	46	43	32	31	25	24	20	44	42	32	31	25	24	20	31	30
	0.6	63	58	48	46	40	39	33	61	57	48	45	39	38	33	46	44
	0.8	73	66	58	55	49	47	41	71	65	57	54	48	46	41	54	52
	1	82	74	67	63	58	55	49	79	72	66	62	57	54	49	63	59
	1.25	90	80	77	70	67	63	57	87	78	75	69	66	62	57	71	67
	1.5	95	84	83	75	73	68	62	92	82	80	74	72	67	62	76	71
	2	103	90	92	82	83	76	71	99	88	89	81	81	75	70	84	78
	2.5	108	94	99	87	91	82	77	104	92	95	86	88	81	76	90	83
	3	112	96	103	90	96	85	81	107	94	100	89	93	84	80	93	86
	4	116	99	109	95	103	91	87	112	97	105	93	100	89	86	98	90
	5	119	101	113	97	108	94	91	114	99	109	96	104	93	90	102	93
	7	123	103	118	100	114	98	95	118	101	114	99	110	96	94	105	96
	10	125	105	122	103	119	101	99	120	103	117	101	114	99	98	108	98

配光曲線



直射水平面照度

