



ECOHiLUX照明器具 配光データシート			
器具品名	ラインルクス	保守率	
		良	0.81
器具品番	LXBF-UK40-W170	中	0.77
部品品名	-	否	0.68
部品品番	-	器具効率	
器具光束	6225lm	上方向	0%
光源	LXU160F-65D-40S	下方向	100%
光源光束	6555lm	全方向	100%



照明率表

		作業面照明率(×0.01)															
反射率	天井	80								70							
	壁	70				50				30				10			
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10
室指数	0.4	45	42	31	30	24	23	19	44	41	31	30	24	23	19	30	29
	0.6	62	57	47	45	38	37	32	60	56	47	44	38	37	32	45	43
	0.8	72	66	57	54	48	46	40	70	64	56	53	47	45	40	54	52
	1	81	73	67	62	57	54	48	79	71	65	61	56	53	48	62	59
	1.25	90	80	76	70	66	62	56	87	78	74	69	65	62	56	71	67
	1.5	95	84	82	75	73	67	62	92	82	80	73	71	67	61	76	71
	2	103	90	92	82	83	76	70	99	88	89	81	81	75	70	85	79
	2.5	108	94	99	87	91	82	77	105	92	96	86	88	81	76	91	84
	3	112	96	103	90	96	86	81	108	94	100	89	93	85	81	94	87
	4	117	99	110	95	103	91	87	112	98	106	94	100	90	86	100	91
	5	120	101	114	98	108	94	91	115	100	110	96	105	93	90	103	94
	7	123	104	119	101	114	98	96	118	102	115	100	111	97	95	107	97
	10	126	105	122	103	119	102	100	121	104	118	102	115	100	99	110	100

配光曲線



直射水平面照度

