


## ECOHiLUX照明器具 配光データシート

## 意匠図


器具品名	ラインルクス	保守率
器具品番	LXBF-CH40	良
部品品名	-	中
部品品番	-	否
器具光束	4940lm	器具効率
光源	LXU160F-49D-40S	上方向
光源光束	4940lm	下方向
		全方向



## 照明率表

作業面照明率(×0.01)																0	
反射率	天井	80				70				50				30			
	壁	70	50	30	10	70	50	30	10	50	30	10	30	10	10	30	
室 指 数	床	30	10	30	10	30	10	30	10	30	10	10	30	10	10	30	0
	0.4	45	42	31	30	24	23	19	44	41	31	30	24	23	19	29	22
	0.6	62	57	47	45	38	37	32	60	55	46	44	38	37	31	44	36
	0.8	72	65	57	53	47	45	39	69	63	55	52	46	44	39	53	43
	1	81	72	66	61	56	53	47	77	70	64	60	55	52	46	61	51
	1.25	89	79	75	69	65	61	55	85	77	73	67	64	60	55	69	59
	1.5	94	83	81	73	71	66	60	90	81	78	72	69	65	60	74	66
	2	102	89	90	81	81	74	69	98	86	87	79	79	73	68	82	71
	2.5	107	93	97	86	89	80	75	103	90	94	84	86	79	74	87	81
	3	111	95	102	89	94	84	79	106	93	98	87	91	82	78	91	84
5	4	115	98	108	93	101	89	85	110	96	104	92	98	88	84	96	88
	5	118	100	112	96	106	93	89	113	98	108	94	103	91	88	100	91
	7	122	103	117	100	113	97	94	117	100	112	98	108	95	93	104	94
	10	125	104	121	102	118	100	98	119	102	116	100	113	98	97	107	97

## 配光曲線



## 直射水平面照度

