


## ECOHiLUX照明器具 配光データシート

品名	ラインルクス	保守率	
セット品番	LX190F-57L-TR110T	良	0.83
器具品名	トラフ型	中	0.81
器具品番	LXBF-TR110T	否	0.77
器具光束	5760lm	器具効率	
光源	LXU190F-57L-110T	上方向	4%
光源光束	5760lm	下方向	96%
		全方向	100%


## 意匠図



## 照度率表

作業面照度率( $\times 0.01$ )																	
反射率	天井	80				70				50				30			
	壁	70	50	30	10	70	50	30	10	50	30	10	30	10	10	30	
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	
室指數	0.4	46	43	32	31	25	24	20	44	42	32	31	25	24	20	19	17
	0.6	63	58	48	46	40	39	33	61	57	48	45	39	38	33	37	32
	0.8	73	66	58	55	49	47	41	71	65	57	54	48	46	41	54	45
	1	82	74	67	63	58	55	49	79	72	66	62	57	54	49	55	44
	1.25	90	80	77	70	67	63	57	87	78	75	69	66	62	57	63	52
	1.5	95	84	83	75	73	68	62	92	82	80	74	72	67	62	76	64
	2	103	90	92	82	83	76	71	99	88	89	81	81	75	70	84	71
	2.5	108	94	99	87	91	82	77	104	92	95	86	88	81	76	90	83
	3	112	96	103	90	96	85	81	107	94	100	89	93	84	80	93	82
	4	116	99	109	95	103	91	87	112	97	105	93	100	89	86	98	87
10	5	119	101	113	97	108	94	91	114	99	109	96	104	93	90	102	90
	7	123	103	118	100	114	98	95	118	101	114	99	110	96	94	105	92
	10	125	105	122	103	119	101	99	120	103	117	101	114	99	98	108	95

## 配光曲線



## 直射水平面照度

