

ECOHiLUX照明器具 配光データシート

意匠図


品名	ラインルクス	保守率	
セット品番	LX190F-28WW-WW40-D	良	0.69
器具品名	ウォールウォッシャー型	中	0.67
器具品番	LXBF-WW40-D	否	0.63
器具光束	2880lm	器具効率	
光源	LXU190F-29WW-40S-D	上方向	0%
光源光束	2940lm	下方向	98%
		全方向	98%



照明率表

		作業面照明率(×0.01)															
反射率	天井	80								70							
	壁	70				50				30				10			
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10
室 指 数	0.4	43	40	29	28	22	21	17	41	39	29	28	21	16	27	27	21
	0.6	59	54	44	42	35	34	28	57	53	43	41	34	33	28	41	39
	0.8	69	62	53	50	43	41	35	66	60	52	49	42	41	35	49	47
	1	77	69	62	57	51	49	42	74	67	60	56	50	48	42	57	54
	1.25	85	76	71	65	60	57	50	82	73	69	63	59	56	50	65	61
	1.5	90	80	76	69	66	62	55	87	77	74	68	65	61	55	70	65
	2	98	85	86	77	76	70	64	94	83	83	75	74	68	63	78	72
	2.5	104	89	93	82	84	75	70	99	87	89	80	81	74	69	83	77
	3	107	92	97	85	89	79	74	103	90	94	84	86	78	73	87	80
	4	112	95	104	90	97	85	80	107	93	100	88	93	84	79	93	85
	5	115	97	108	93	102	89	85	110	95	104	91	98	87	84	96	88
	7	119	100	113	96	108	93	90	114	98	109	95	104	92	89	101	91
	10	122	102	118	99	114	97	94	117	100	113	98	109	95	93	104	94

配光曲線



直射水平面照度

