


# ECOHiLUX照明器具 配光データシート

## 意匠図

品名	LEDベースライト			保守率	
セット品番	LX3-170-117WW-UK110T-W170-LI			良	0.81
光源品番	LX3U170-123WW-110T-LI			中	0.77
器具品番	LXBF-UK110T-W170			否	0.68
器具光束	11715lm	最大取付間隔		器具効率	
光源	LED	A-A	1.34 H	上方向	0%
光源光束	12330lm	B-B	1.25 H	下方向	100%
				全方向	100%




## 照明率表

作業面照明率(×0.01)

反(射率)	天井	80						70						50			30			0			
		壁	70	50	30	10	10	70	50	30	10	10	50	30	10	10	30	10	10	0			
0.4	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	18	
0.6		46	43	32	31	25	24	20	44	42	32	31	24	24	20	31	30	24	24	20	24	23	19
0.8		63	58	49	46	40	39	33	61	57	48	46	40	38	33	46	45	39	38	33	38	37	33
1		74	67	59	55	49	47	42	71	65	58	55	49	47	41	56	53	48	46	41	47	46	41
1.25		83	74	68	63	59	56	50	80	73	67	63	58	55	50	64	61	56	54	49	55	54	49
1.5		91	81	78	71	69	64	59	88	79	76	71	67	64	58	73	69	66	63	58	64	62	58
2		96	85	84	76	75	69	64	93	83	82	75	73	69	64	78	73	71	68	63	69	67	63
2.5		104	91	93	84	85	78	73	101	89	91	82	83	77	72	86	80	80	76	71	77	74	71
3		110	95	100	89	93	83	79	106	93	97	87	91	83	79	92	85	87	81	78	83	80	77
4		113	97	105	92	98	87	83	109	95	102	91	95	86	83	96	88	91	85	82	87	83	81
5		117	100	111	96	105	92	89	113	98	107	95	102	91	88	101	93	97	90	87	92	88	86
7		120	102	115	99	110	96	93	116	100	111	97	107	95	92	104	95	101	93	91	96	91	89
10		124	104	119	102	116	99	97	119	103	115	100	112	98	96	108	98	106	96	95	100	95	93
		126	105	123	104	120	102	101	121	104	119	103	116	101	100	111	100	109	99	98	103	97	96

## 配光曲線



## 直射水平面照度

