


ECOHiLUX照明器具 配光データシート

意匠図


品名	スクエアパネル照明			保守率	
				良	0.77
セット品番	SQP-12WW47-CL72-LI			中	0.72
光源品番	SQPL12WW47LI			否	0.68
器具品番	SQPBCL72			器具効率	
器具光束	11500 lm	最大取付間隔		上方向	2%
光源	LED	AA	1.32H	下方向	99%
光源光束	11500 lm	BB	1.32H	全方向	100%



照明率表

作業面照明率(×0.01)																											
反射率(%)	天井	80								70								50						30			0
	壁	70			50		30		10	70		50		30		10	50		30		10	30		10	0		
	床	30	10	30	10	30	10	10	30	10	30	10	30	10	10	30	10	30	10	10	30	10	10	30	0		
室 指 数	0.4	45	42	31	30	24	23	19	44	41	31	30	24	23	19	30	29	23	23	19	23	23	19	23	17		
	0.6	62	57	47	45	39	37	32	60	56	47	44	38	37	32	45	43	37	37	32	37	36	32	30	30		
	0.8	72	66	57	54	48	46	40	70	64	56	53	47	45	40	54	52	46	45	39	45	44	39	37	37		
	1	81	73	67	62	57	54	48	78	71	65	61	56	53	48	62	59	54	52	47	53	52	47	44	44		
	1.25	90	80	76	70	66	62	57	86	78	74	69	65	62	56	71	67	63	61	56	61	59	55	53	53		
	1.5	95	84	82	74	73	67	62	91	82	80	73	71	67	61	76	71	69	65	61	66	64	60	57	57		
	2	103	89	91	82	83	76	70	99	88	89	81	81	75	70	84	78	78	73	69	74	72	68	65	65		
	2.5	108	93	98	87	90	81	77	104	91	95	86	88	81	76	90	83	84	79	75	81	77	74	71	71		
	3	111	96	103	90	95	85	81	107	94	100	89	93	84	80	94	86	89	82	79	84	81	78	75	75		
	4	116	99	109	94	103	90	87	112	97	105	93	100	89	86	99	91	95	87	85	90	86	83	80	80		
	5	119	101	113	97	108	94	91	114	99	109	96	105	93	90	102	93	99	91	88	93	89	87	83	83		
	7	122	103	118	100	114	98	95	118	101	114	99	110	97	94	106	96	103	94	93	97	92	91	88	88		
10	125	105	122	103	119	101	99	120	103	117	101	115	100	98	109	99	107	97	96	101	95	94	91	91			

配光曲線



直射水平面照度

