


ECOHiLUX照明器具 配光データシート

意匠図


品名	LEDベースライト			保守率	
セット品番	LX4-190-32WW-CL40			良	0.83
光源品番	LX4U190-32WW-40S			中	0.81
器具品番	LXBF-CL40			否	0.77
器具光束	3105 lm	最大取付間隔		器具効率	
光源	LED	AA	1.65H	上方向	4%
光源光束	3105 lm	BB	1.30H	下方向	96%
				全方向	100%



照明率表

作業面照明率(×0.01)																												
反射率(%)	天井	80								70								50						30				0
	壁	70			50		30			10	70		50		30		10	50		30		10	30		10	0		
	床	30	10	30	10	30	10	10	30	10	30	10	30	10	10	30	10	30	10	10	30	10	10	30	10	0		
室 指 数	0.4	44	42	31	30	23	23	18	43	40	30	29	23	23	18	29	28	22	22	18	22	22	18	22	18	16		
	0.6	61	56	46	44	37	36	31	59	55	45	43	37	36	31	43	42	36	35	30	35	34	30	34	28			
	0.8	71	64	56	52	46	44	38	68	63	55	51	45	44	38	52	50	44	43	38	43	42	37	34				
	1	79	71	65	60	55	52	46	77	69	63	59	54	51	46	60	57	52	50	45	50	49	44	41				
	1.25	88	78	74	68	64	60	54	84	76	72	67	63	59	54	68	64	60	58	53	58	56	52	49				
	1.5	93	82	80	73	70	65	59	89	80	78	71	69	64	59	73	69	66	63	58	63	61	57	54				
	2	101	88	89	80	80	73	68	97	86	86	78	78	72	67	81	75	74	70	66	71	68	64	61				
	2.5	106	92	96	85	88	79	74	102	89	93	83	85	78	73	87	80	81	76	72	77	74	70	67				
	3	110	94	100	88	93	83	78	105	92	97	86	90	82	77	91	83	85	79	76	81	77	74	70				
	4	114	97	107	92	100	88	84	109	95	103	91	97	87	83	96	88	91	84	81	86	82	79	76				
	5	117	99	111	95	105	91	88	112	97	107	94	102	90	87	99	90	95	88	85	89	85	83	79				
7	121	101	116	98	111	96	93	116	100	111	97	107	94	92	103	94	100	91	89	94	89	87	83					
10	123	103	120	101	116	99	97	118	101	115	99	112	97	96	106	96	104	95	93	97	92	90	86					

配光曲線



直射水平面照度

