

ECOHiLUX照明器具 配光データシート

意匠図

| | | | | | | |
|-------|-----------------------|--------|-------|------|------|----|
| 品名 | LEDベースライト | | | 保守率 | | |
| セット品番 | LX4-190-20N-CH40-W250 | | | 良 | 0.83 | |
| 光源品番 | LX4U190-20N-40S | | | 中 | 0.81 | |
| 器具品番 | LXBF-CH40-W250 | | | 否 | 0.77 | |
| | | | | 器具効率 | | |
| 器具光束 | 2000 lm | 最大取付間隔 | | | 上方向 | 1% |
| 光源 | LED | AA | 1.32H | 下方向 | 100% | |
| 光源光束 | 2000 lm | BB | 1.63H | 全方向 | 100% | |



照明率表

| 作業面照明率(×0.01) | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---------------|------|-----|-----|-----|-----|-----|----|-----|-----|-----|-----|-----|----|----|-----|----|-----|----|----|-----|----|----|----|----|----|---|
| 反射率(%) | 天井 | 80 | | | | | | | | 70 | | | | | | | | 50 | | | | 30 | | 0 | | |
| | 壁 | 70 | | 50 | | 30 | | 10 | | 70 | | 50 | | 30 | | 10 | | 50 | | 30 | | 10 | | 30 | 10 | 0 |
| | 床 | 30 | 10 | 30 | 10 | 30 | 10 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 10 | 30 | 10 | 10 | 0 |
| 室 指 数 | 0.4 | 45 | 42 | 31 | 30 | 24 | 23 | 19 | 44 | 41 | 31 | 30 | 23 | 23 | 19 | 30 | 29 | 23 | 23 | 18 | 23 | 22 | 18 | 17 | | |
| | 0.6 | 62 | 57 | 47 | 45 | 38 | 37 | 31 | 60 | 55 | 46 | 44 | 38 | 36 | 31 | 44 | 43 | 37 | 36 | 31 | 36 | 35 | 31 | 29 | | |
| | 0.8 | 72 | 65 | 57 | 53 | 47 | 45 | 39 | 69 | 64 | 55 | 52 | 46 | 45 | 39 | 53 | 51 | 45 | 44 | 39 | 44 | 43 | 38 | 36 | | |
| | 1 | 80 | 72 | 66 | 61 | 56 | 53 | 47 | 78 | 70 | 64 | 60 | 55 | 52 | 47 | 61 | 58 | 53 | 51 | 46 | 52 | 51 | 46 | 43 | | |
| | 1.25 | 89 | 79 | 75 | 69 | 65 | 61 | 55 | 86 | 77 | 73 | 68 | 64 | 60 | 55 | 70 | 66 | 62 | 59 | 54 | 60 | 58 | 54 | 51 | | |
| | 1.5 | 94 | 83 | 81 | 73 | 71 | 66 | 60 | 91 | 81 | 79 | 72 | 70 | 65 | 60 | 75 | 70 | 67 | 64 | 59 | 65 | 63 | 58 | 56 | | |
| | 2 | 102 | 88 | 90 | 80 | 81 | 74 | 68 | 98 | 87 | 88 | 79 | 79 | 73 | 68 | 83 | 77 | 76 | 72 | 67 | 73 | 70 | 66 | 64 | | |
| | 2.5 | 107 | 92 | 97 | 86 | 88 | 80 | 75 | 103 | 91 | 94 | 84 | 86 | 79 | 74 | 89 | 82 | 83 | 77 | 73 | 79 | 76 | 72 | 70 | | |
| | 3 | 110 | 95 | 101 | 89 | 94 | 84 | 79 | 106 | 93 | 98 | 88 | 91 | 83 | 78 | 93 | 85 | 87 | 81 | 77 | 83 | 79 | 76 | 73 | | |
| | 4 | 115 | 98 | 108 | 93 | 101 | 89 | 85 | 111 | 96 | 104 | 92 | 98 | 88 | 84 | 98 | 89 | 93 | 86 | 83 | 88 | 84 | 81 | 79 | | |
| 5 | 118 | 100 | 112 | 96 | 106 | 92 | 89 | 114 | 98 | 108 | 95 | 103 | 91 | 88 | 101 | 92 | 97 | 89 | 87 | 92 | 87 | 85 | 82 | | | |
| 7 | 122 | 102 | 117 | 99 | 112 | 96 | 94 | 117 | 101 | 113 | 98 | 109 | 95 | 93 | 105 | 96 | 102 | 93 | 91 | 96 | 91 | 89 | 86 | | | |
| 10 | 124 | 104 | 121 | 102 | 117 | 100 | 98 | 120 | 103 | 116 | 101 | 113 | 99 | 97 | 109 | 98 | 106 | 96 | 95 | 100 | 94 | 93 | 90 | | | |

配光曲線



直射水平面照度

