


ECOHiLUX照明器具 配光データシート

意匠図


|       |                            |        |       |      |      |
|-------|----------------------------|--------|-------|------|------|
| 品名    | LEDベースライト                  |        |       | 保守率  |      |
| セット品番 | LX4-190-52L-UK40-W328RP-LI |        |       | 良    | 0.81 |
| 光源品番  | LX4U190-52L-40S-LI         |        |       | 中    | 0.77 |
| 器具品番  | LXBF-UK40-W328RP           |        |       | 否    | 0.68 |
| 器具光束  | 4700 lm                    | 最大取付間隔 |       | 器具効率 |      |
| 光源    | LED                        | AA     | 1.32H | 上方向  | 0%   |
| 光源光束  | 4795 lm                    | BB     | 1.64H | 下方向  | 100% |
|       |                            |        |       | 全方向  | 100% |



照明率表

| 作業面照明率(×0.01) |      |     |     |     |     |     |     |     |     |     |     |     |     |    |     |     |     |     |    |     |    |    |    |    |    |    |  |   |
|---------------|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|-----|-----|-----|-----|----|-----|----|----|----|----|----|----|--|---|
| 反射率<br>(%)    | 天井   | 80  |     |     |     |     |     |     |     | 70  |     |     |     |    |     |     |     | 50  |    |     |    |    |    | 30 |    |    |  | 0 |
|               | 壁    | 70  |     |     | 50  |     | 30  |     |     | 10  | 70  |     | 50  |    | 30  |     | 10  | 50  |    | 30  |    | 10 | 30 |    | 10 | 0  |  |   |
|               | 床    | 30  | 10  | 30  | 10  | 30  | 10  | 10  | 30  | 10  | 30  | 10  | 30  | 10 | 10  | 30  | 10  | 30  | 10 | 10  | 30 | 10 | 10 | 30 | 10 | 0  |  |   |
| 室<br>指<br>数   | 0.4  | 45  | 42  | 32  | 31  | 24  | 24  | 19  | 44  | 41  | 31  | 30  | 24  | 24 | 19  | 30  | 29  | 24  | 23 | 19  | 23 | 23 | 19 | 23 | 19 | 17 |  |   |
|               | 0.6  | 62  | 57  | 48  | 45  | 39  | 38  | 32  | 61  | 56  | 47  | 45  | 38  | 37 | 32  | 45  | 44  | 38  | 37 | 32  | 37 | 36 | 32 | 32 | 30 |    |  |   |
|               | 0.8  | 73  | 66  | 58  | 54  | 48  | 46  | 40  | 70  | 64  | 56  | 53  | 47  | 46 | 40  | 54  | 52  | 46  | 45 | 40  | 45 | 44 | 39 | 37 |    |    |  |   |
|               | 1    | 81  | 73  | 67  | 62  | 57  | 54  | 48  | 79  | 71  | 65  | 61  | 56  | 54 | 48  | 63  | 59  | 55  | 53 | 48  | 53 | 52 | 47 | 45 |    |    |  |   |
|               | 1.25 | 90  | 80  | 76  | 70  | 67  | 62  | 57  | 87  | 78  | 74  | 69  | 66  | 62 | 56  | 71  | 67  | 64  | 61 | 56  | 62 | 60 | 55 | 53 |    |    |  |   |
|               | 1.5  | 95  | 84  | 82  | 75  | 73  | 68  | 62  | 92  | 82  | 80  | 74  | 71  | 67 | 62  | 76  | 72  | 69  | 66 | 61  | 67 | 65 | 60 | 58 |    |    |  |   |
|               | 2    | 103 | 90  | 92  | 82  | 83  | 76  | 70  | 99  | 88  | 89  | 81  | 81  | 75 | 70  | 85  | 79  | 78  | 74 | 69  | 75 | 72 | 69 | 66 |    |    |  |   |
|               | 2.5  | 108 | 93  | 99  | 87  | 91  | 82  | 77  | 104 | 92  | 96  | 86  | 89  | 81 | 77  | 91  | 84  | 85  | 79 | 76  | 81 | 78 | 75 | 72 |    |    |  |   |
|               | 3    | 112 | 96  | 103 | 90  | 96  | 86  | 81  | 108 | 94  | 100 | 89  | 94  | 85 | 81  | 95  | 87  | 89  | 83 | 80  | 85 | 82 | 79 | 76 |    |    |  |   |
|               | 4    | 116 | 99  | 109 | 95  | 103 | 91  | 87  | 112 | 98  | 106 | 94  | 100 | 90 | 87  | 100 | 91  | 95  | 88 | 85  | 91 | 87 | 84 | 81 |    |    |  |   |
|               | 5    | 119 | 101 | 114 | 98  | 108 | 94  | 91  | 115 | 100 | 110 | 96  | 105 | 93 | 90  | 103 | 94  | 99  | 91 | 89  | 94 | 90 | 88 | 85 |    |    |  |   |
|               | 7    | 123 | 103 | 118 | 101 | 114 | 98  | 96  | 118 | 102 | 114 | 100 | 111 | 97 | 95  | 107 | 97  | 104 | 95 | 93  | 99 | 93 | 92 | 89 |    |    |  |   |
| 10            | 126  | 105 | 122 | 103 | 119 | 101 | 100 | 121 | 104 | 118 | 102 | 115 | 100 | 99 | 110 | 100 | 108 | 98  | 97 | 102 | 96 | 95 | 92 |    |    |    |  |   |

配光曲線



直射水平面照度

