

品名

IR-DN-3475

光源

LDA8L-G-E17-6T5

実効光束
(器具光束)

247lm

エネルギー
効率

42.3lm/W

配光曲線図

実光度

A ——— A' 0° - 180°
B - - - - - B' 45° - 135°
C - - - - - C' 90° - 270°

180°
150°
120°
90°
60°
30°
0°
30°
60°
90°
120°
150°

100 cd
200 cd
300 cd
400 cd
500 cd

1/2照度角

直射水平面照度

単位：Lx

器具効率	32.5%	
色温度	電球色	
演色評価指数	—	
保守率	良	0.69
	中	0.67
	否	0.63
1/2ビーム角		
A-A'	53.0	Deg
C-C'	53.0	Deg
最大取付間隔		
A-A'	0.81	H
C-C'	0.81	H

1M	φ 808	263 LX	200
2M	φ 1616	66 LX	100
3M	φ 2424	29 LX	50
4M	φ 3232	16 LX	20

固有照明率表																		
天井	80%				70%				50%				30%				0%	
壁	70%	50%	30%	10%	70%	50%	30%	10%	70%	50%	30%	10%	70%	50%	30%	10%	0%	
床	10%				10%				10%				10%				0%	
0.60	77	70	65	61	76	69	64	61	75	68	64	61	73	68	64	61	59	
0.80	84	77	72	69	83	77	72	69	82	76	71	68	80	75	71	68	67	
1.00	90	83	79	75	89	83	79	75	87	82	78	75	85	81	77	75	73	
1.25	94	89	84	81	93	88	84	81	91	87	83	81	89	85	82	80	78	
1.50	97	92	88	85	96	91	88	85	94	90	87	84	92	89	86	84	82	
2.00	101	97	94	92	100	97	94	92	98	95	93	91	96	93	92	90	88	
2.50	103	100	98	96	102	100	97	95	100	98	96	94	98	96	95	93	91	
3.00	105	102	100	99	104	102	100	98	102	100	98	97	100	98	97	96	94	
4.00	106	104	103	102	105	103	102	101	103	102	101	99	101	100	99	98	96	
5.00	107	106	104	103	106	105	103	102	104	103	102	101	102	101	100	99	97	
7.00	108	107	106	105	107	106	105	104	105	104	103	103	103	102	101	101	98	
10.00	108	108	107	107	107	107	106	106	105	105	104	104	103	103	102	102	99	