


ECOHiLUX照明器具 配光データシート


| | | | |
|------|------------------|------|------|
| 器具品名 | グレアレスダウンライト | 保守率 | |
| 器具品番 | DL25L279-10G4W-D | 良 | 0.69 |
| 部品品名 | - | 中 | 0.67 |
| 部品品番 | - | 否 | 0.63 |
| 器具光束 | 1990lm | 器具効率 | |
| 光源 | - | 上方向 | 0% |
| 光源光束 | 一体型器具のため、器具光束表示 | 下方向 | 100% |
| | | 全方向 | 100% |



照明率表

| 反射率 | | 作業面照明率(×0.01) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|-----|---|---------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|--|----|--|---|--|--|--|----|--|--|--|--|--|--|--|---|--|--|--|--|--|--|--|
| | | 天井 | | | | | | | | 80 | | | | | | | | 70 | | | | | | | | 50 | | | | | | | | 30 | | | | | | | | 0 | | | | | | | |
| | | 壁 | | 70 | | 50 | | 30 | | 10 | | 70 | | 50 | | 30 | | 10 | | 50 | | 30 | | 10 | | 30 | | 10 | | 0 | | | | | | | | | | | | | | | | | | | |
| 室 | 指 | 0.4 | 67 | 63 | 57 | 55 | 51 | 50 | 47 | 66 | 63 | 56 | 55 | 51 | 50 | 47 | 56 | 54 | 50 | 50 | 47 | 50 | 49 | 47 | 45 | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 0.6 | 86 | 80 | 76 | 72 | 70 | 68 | 65 | 85 | 79 | 75 | 72 | 70 | 68 | 65 | 74 | 71 | 69 | 67 | 64 | 68 | 67 | 64 | 63 | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 0.8 | 96 | 88 | 87 | 81 | 80 | 77 | 74 | 95 | 87 | 86 | 81 | 80 | 77 | 74 | 84 | 80 | 79 | 76 | 74 | 77 | 76 | 73 | 72 | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 1 | 103 | 92 | 93 | 87 | 87 | 83 | 80 | 100 | 91 | 92 | 86 | 86 | 82 | 79 | 90 | 85 | 85 | 82 | 79 | 83 | 81 | 79 | 77 | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 1.25 | 108 | 96 | 100 | 91 | 93 | 88 | 85 | 106 | 95 | 98 | 91 | 92 | 87 | 85 | 95 | 89 | 90 | 86 | 84 | 88 | 86 | 84 | 82 | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 1.5 | 112 | 98 | 104 | 94 | 98 | 91 | 88 | 109 | 97 | 102 | 93 | 96 | 90 | 88 | 98 | 92 | 94 | 89 | 87 | 91 | 88 | 86 | 85 | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 2 | 116 | 101 | 109 | 98 | 104 | 95 | 92 | 113 | 100 | 107 | 97 | 102 | 94 | 92 | 103 | 95 | 99 | 93 | 91 | 96 | 92 | 90 | 89 | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 2.5 | 119 | 103 | 113 | 100 | 108 | 98 | 96 | 116 | 102 | 111 | 99 | 106 | 97 | 95 | 106 | 98 | 102 | 96 | 94 | 99 | 95 | 93 | 91 | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 3 | 122 | 104 | 116 | 102 | 112 | 100 | 98 | 118 | 103 | 113 | 101 | 109 | 99 | 97 | 108 | 99 | 105 | 98 | 96 | 101 | 96 | 95 | 93 | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 4 | 125 | 106 | 120 | 104 | 117 | 103 | 101 | 121 | 105 | 117 | 103 | 114 | 102 | 101 | 111 | 102 | 109 | 100 | 99 | 104 | 99 | 98 | 96 | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 5 | 127 | 107 | 123 | 106 | 120 | 105 | 103 | 122 | 106 | 119 | 105 | 117 | 104 | 103 | 113 | 103 | 111 | 102 | 101 | 106 | 100 | 100 | 97 | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 7 | 129 | 108 | 126 | 107 | 124 | 107 | 106 | 124 | 107 | 122 | 106 | 121 | 106 | 105 | 115 | 105 | 114 | 104 | 104 | 108 | 102 | 102 | 99 | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 10 | 130 | 109 | 129 | 109 | 128 | 108 | 108 | 126 | 108 | 125 | 108 | 123 | 107 | 107 | 117 | 106 | 116 | 105 | 105 | 110 | 104 | 103 | 101 | | | | | | | | | | | | | | | | | | | | | | | | |

配光曲線



直射水平面照度

